



INSTRUCTION MANUAL

Your Exclusive Professional Carrying Bag is equipped with an adjustable, elasticized cord that you can use to easily attach your RC car to the top of the bag.

- 1 Remove sleeve from cord. →



- 2 Pass loop of cord under carrying handle (opposite side from telescopic pull handle)



- 3 Fold loop over carrying handle, then pass end of cord through loop



- 4 Pull cord tight, then spread loop to sides of carrying handle



- 5 Pass end of cord beneath carrying handle on other side of bag



- 6 Spread end of cord around telescopic pull handle



- 7 Slide plastic collar up cords to tighten



- 8 Install sleeve



- 9

FINAL ASSEMBLY VIEW





Your Exclusive Professional Carrying Bag is equipped with straps and buckles to attach two accessory bags (such as the HUDY Starter Box Bag and/or HUDY Transmitter Bag).

- 1** Unlock the clips of the bag side strap.



- 2** Open one top buckle.



- 3** Pass the strap through either the plastic top loop of the accessory bag (comes as stock on HUDY bags as shown) or the top handle (of another bag).



- 4** Pass the free end of the strap upwards through one of the slots in the top buckle as shown.



- 5** Pull the strap tight, then close the top buckle.



- 6** Repeat steps 2-5 to attach another accessory bag to the other strap. With accessory bag(s) in place, reconnect the side strap and adjust as required.



- 7** FINAL ASSEMBLED VIEW





TECH TIP

Your Exclusive Professional Carrying Bag is equipped with a telescopic handle with load capacity limitations depending on the length of extension. DO NOT overload your bag. Please follow the suggestions below. ATTENTION! Failure to do so may cause damage to the telescopic handle, which is not covered by HUDY Warranty.

Handle fully extended.

Maximum load capacity:

15kg/33lb



Handle extended to 1/2 length.

Maximum load capacity:

20kg/44lb



Handle not extended.

Maximum load capacity:

25kg/55lb



INCORRECT



CORRECT

